



**www.tkm.ru**

**ДЗДЗДЗ**

# NetUSB-400i

\$136.55 (ÑfÑ†Đ,Ñ,Ñ«Đ²Đ°Ñ• Đ½Đ°Đ»Đ¾Đ³Đ, 18 %)

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 506.01 cm /l2 Do Q Đ£Đ½Ñ€Đ°Đ²Đ»ĐµĐ½Đ, Đµ 4-Đ¼Ñ• ÑfÑ•Ñ,Ñ€Đ¾Đ¹Ñ•Ñ,Đ²Đ°Đ¼Đ, USB 2.0 Ñ†ĐµÑ€ĐµĐ• Đ»Đ¾Đ°Đ»Ñ€Đ½ÑfÑž Ñ•ĐµÑ,Ñ€

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 449.31 cm /l2 Do Q ĐµÑ,ĐµĐ²Đ¾Đ¹ Đ,Đ½Ñ,ĐµÑ€Ñ,„ĐµĐ¹Ñ• 10BaseT/100BaseTX/1000BaseTX Auto-detecting

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 406.79 cm /l2 Do Q Đ”Ñ€Đ°Đ¹Đ²ĐµÑ€ Đ°Đ²Ñ,Đ¾Đ¼Đ°Ñ,Đ,Ñ†ĐµÑ•Đ°Đ, Đ½Đ°Ñ...Đ¾Đ´Đ,Ñ, USB Ñ•ĐµÑ€Đ²ĐµÑ€Ñ‹ Đ² Ñ•ĐµÑ,Đ,

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 364.27 cm /l2 Do Q ĐŸĐ¾Đ´Đ´ĐµÑ€Đ¶Đ°Đ° Windows 8.1, 8, 7, 2003, XP, Vista (64 Đ, 32 Đ±Đ,Ñ,)

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 321.75 cm /l2 Do Q Đ•Đ²Ñ,Đ¾Đ¼Đ°Ñ,Đ,Ñ†ĐµÑ•Đ°Đ¾Đµ Đ¿Đ¾Đ´Đ°Đ»ÑžÑ†ĐµĐ½Đ,Đµ Đ, Đ¾Ñ,Đ°Đ»ÑžÑ†ĐµĐ½Đ,Đµ Đ¿Ñ€Đ,Đ½Ñ,ĐµÑ€Đ¾Đ²

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 265.06 cm /l2 Do Q Đ•Đ²Ñ,Đ¾Đ¼Đ°Ñ,Đ,Ñ†ĐµÑ•Đ°Đ,Đ¹ Đ•Đ°Đ¿ÑfÑ•Đ° Đ½ĐµĐ¾Đ±Ñ...Đ¾Đ´Đ,Đ¼Đ¾Đ¾Đ¾ Đ¿Ñ€Đ¾Đ»Đ¾Đ¶ĐµĐ½Đ,Ñ• Đ¿Ñ€Đ, Đ¿Đ¾Đ´Đ°Đ»ÑžÑ†ĐµĐ½Đ,Đ, Đ¾Đ¿Ñ€ĐµĐ´ĐµĐ»Ñ¹Đ½Đ½Đ¾Đ¾Đ¾ÑfÑ•Ñ,Ñ€Đ¾Đ¹Ñ•Ñ,Đ²Đ°

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 194.19 cm /l2 Do Q ĐŸĐ¾Đ´Đ´ĐµÑ€Đ¶Đ,Đ²Đ°ĐµÑ, Ñ•Đ»ĐµĐ´ÑfÑžÑ%Đ,Đµ Ñ,Đ,Đ¿Ñ‹ USB ÑfÑ•Ñ,Ñ€Đ¾Đ¹Ñ•Ñ,Đ²: bulk, interrupt, isochronous

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 137.50 cm /l2 Do Q Đ´Đ»Đ¾Đ° Đ¿Đ,Ñ,Đ°Đ½Đ,Ñ• 12Đ¹ 1Đ• Đ² Đ°Đ¾Đ¼Đ¿Đ»ĐµĐ°Ñ,Đµ

İ½İ½İ½type=image,ypos=5,width=1.3225,height=1.3225İ½İ½İ½q 3.75 0 0 3.75 28.35 94.98 cm /l2 Do Q

ƐœƐµŃ,Ɛ°Ɛ»Ɛ»Ɛ,Ń‡ƐµŃ•Ɛ°Ɛ,Ɛ¹ Ɛ°Ɛ¾Ń€Ɛ;ŃƒŃ•

Ɛ;Ɛ;ƐµŃ†Ɛ,Ń,,Ɛ,Ɛ°Ɛ°Ń†Ɛ,Ń•

**Ɛ°Ɛ,Ɛ½Ɛ° USB**

Ɛ;Ɛ¾Ɛ²Ɛ¼ƐµŃ•Ń,Ɛ,Ɛ¼Ɛ¾Ń•Ń,Ńœ USB 1.1/2.0  
Ɛ;Ɛ°Ɛ¾Ń€Ɛ¾Ń•Ń,Ńœ 480 Mbps, high speed USB2.0  
ƐšƐ¾Ɛ»Ɛ,Ń‡ƐµŃ•Ń,Ɛ²Ɛ¾ 1 RJ-45 Ɛ² 4 USB 2.0  
Ɛ;Ɛ¾Ń€Ń,Ɛ¾Ɛ²

**Ɛ°Ɛ½Ń,ƐµŃ€Ń,,ƐµƐ¹Ń• Ethernet**

ƐœƐ,Ɛ; 10/100/1000Base-T Fast Ethernet  
ƐšƐ¾Ɛ»Ɛ,Ń‡ƐµŃ•Ń,Ɛ²Ɛ¾ 1  
Ɛ;Ɛ¾Ń€Ń,Ɛ¾Ɛ²  
ƐšƐ¾Ɛ½Ɛ½ƐµƐ°Ń,Ɛ¾Ń€ RJ-45

**Ɛ—Ɛ°Ń%Ɛ,Ń,Ɛ°**

ƐŸƐµŃ€ƐµƐ¾Ń€ŃƒƐ•Ɛ°Ɛ° Ɛ;Ɛ¾ 500mA  
Ń,Ɛ¾Ɛ°Ńƒ

**Ɛ;ƐµŃ,Ńœ**

ƐŸŃ€Ɛ¾Ń,Ɛ¾Ɛ°Ɛ¾Ɛ»Ńœ TCP/IP Static IP DHCP  
LED Ɛ,Ɛ½Ɛ°Ɛ,Ɛ°Ɛ°Ń,Ɛ¾Ń€Ńœ Ɛ;Ɛ,Ń•Ń,ƐµƐ¼Ɛ½ŃœƐ¹ Ń•Ń,Ɛ°Ń,ŃƒŃ• Ɛ;ƐµŃ,Ńœ USB Ɛ;Ɛ¾Ń€Ń,Ń•Ń,Ɛ°Ń,ŃƒŃ•

**Ɛ°Ń€Ɛ°Ɛ²ƐµŃ€Ɛ°**

OS Windows 8.1, 8, 7, Vista, 2003, XP, 2000 (32 Ɛ, 64 Ɛ±Ɛ,Ń,)

**Ɛ°Ń•Ń,Ɛ¾Ń‡Ɛ½Ɛ,Ɛ° Ɛ;Ɛ,Ń,Ɛ°Ɛ½Ɛ,Ń•**

Ɛ°Ń...Ɛ¾Ɛ° Ɛ£Ɛ½Ɛ,Ɛ²ƐµŃ€Ń•Ɛ°Ɛ»ŃœƐ½Ɛ¾Ɛµ 9-30Ɛ° Ɛ°Ɛ»Ɛ¾Ɛ°  
Ɛ;Ɛ,Ń,Ɛ°Ɛ½Ɛ,Ń•12VDC, 1A, terminal type Ɛ²  
Ɛ°Ɛ¾Ɛ¼Ɛ;Ɛ;Ɛ»ƐµƐ°Ń,Ɛµ

Ɛ°ŃœŃ...Ɛ¾Ɛ° 500mA Ɛ°Ɛ»Ń• Ɛ°Ɛ°Ɛ¶Ɛ°Ɛ¾Ɛ¾Ɛ¾ USB Ɛ;Ɛ¾Ń€Ń,Ɛ°

**Ɛ°Ń•Ɛ;Ɛ¾Ɛ»Ɛ½ƐµƐ½Ɛ,Ɛµ**

ƐšƐ¾Ń€Ɛ;ŃƒŃ• ƐœƐµŃ,Ɛ°Ɛ»Ɛ»Ɛ,Ń‡ƐµŃ•Ɛ°Ɛ,Ɛ¹ Ɛ°Ɛ¾Ń€Ɛ;ŃƒŃ•. Ɛ;Ɛ°Ɛ¾Ɛ±Ńœ  
Ɛ°Ɛ»Ń• Ɛ°Ń€ƐµƐ;Ɛ»ƐµƐ½Ɛ,Ń• Ɛ½Ɛ° DIN Ń€ƐµƐ°Ɛ°Ńƒ Ɛ²  
Ɛ°Ɛ¾Ɛ¼Ɛ;Ɛ;Ɛ»ƐµƐ°Ń,Ɛµ.

**ƐžƐ°Ń€ŃƒƐ¶ƐµƐ½Ɛ,Ɛµ**

Ɛ Ɛ°Ɛ±Ɛ¾Ń‡Ɛ°Ń• 0 to 55 Â°C (32 to 131 Â°F)  
Ń,ƐµƐ¼Ɛ;ƐµŃ€Ɛ°Ń,ŃƒŃ€Ɛ° 5 to 95% RH  
Ɛ Ɛ°Ɛ±Ɛ¾Ń‡Ɛ°Ń• Ɛ²Ɛ»Ɛ°Ɛ¶Ɛ½Ɛ¾Ń•Ń,Ńœ -20 to 75 Â°C (-4 to 167 Â°F)  
ƐœƐµƐ¼Ɛ;ƐµŃ€Ɛ°Ń,ŃƒŃ€Ɛ° Ń...Ń€Ɛ°Ɛ½ƐµƐ½Ɛ,Ń• EN55022 Class B, EN55024, EN61000-3-2, EN61000-3 IEC  
Ɛ;Ń,Ɛ°Ɛ½Ɛ°Ɛ°Ń€Ń,Ńœ 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC  
Ɛ±ƐµƐ•Ɛ¾Ɛ;Ɛ°Ń•Ɛ½Ɛ¾Ń•Ń,Ɛ, 61000-4-6, IEC 61000-4-8, IEC 61000-4-11. CISPR PUB. 22 and  
FCC Part 15 Class B.

Ń;½Ń;½Ń;½Ńtype=image,ypos=10,xpos=91.957777777778,width=6.0835,height=5.8246276595745Ń;½Ń;½Ń;½Ń

[D—D°D³Ñ€ÑfD·D,Ñ,ÑCE D`D¾D°ÑfD¼DµD½Ñ,D°ÑtD,ÑŽ \(User Manual\) D²Ñ, D¾Ñ€D¼D°Ñ,Dµ PDF](#)

[D"Ñ€D°D¹D²DµÑ€Ñ€, D`D¾D°ÑfD¼DµD½Ñ,D°ÑtD,Ñ• D, D`Ñ€.](#)

[D~D½Ñ, D¾Ñ€D¼D°ÑtD,Ñ• D¾ D;Ñ€D¾D`D°D²ÑtDµ](#)